



Mini Centrifugal DE.

CODE	CAPACITY	SPEED	ST. PRESS	VOLT	POWER	AMP	NOISE
	(CMH)	(RPM)	(Pa)	(V)	(W)	(A)	dB(A)
MC-DE/M075R/1-NO	110-135	2850	105-95	220	25	0.12	50
MC-DE/M100R/1-NO	240-280	2800	136-125	220	40	0.16	57
MC-DE/M125R/1-NO	350-410	2800	340-300	220	90	0.45	59
MC-DE/M150R/1-NO	800-1000	2800	580-525	220	200	1	62
MC-DE/M150R/3-NO	800-1000	2800	580-525	380	200	0.5	62
MC-DE/M160R/1-NO	800-1080	2800	900-700	220	250	2.5	65
MC-DE/M160R/3-NO	800-1080	2800	900-700	380	250	0.68	65
MC-DE/M190R/1/0.75-NO	2100-2300	2800	840-760	220	750	6.2	65
MC-DE/M190R/3/0.75-NO	2100-2300	2800	840-760	380	750	6.2	65
MC-DE/M190R/1-1.1-NO	2300-2100	2800	840-760	220	1100	-	-
MC-DE/M190R/3-1.1-NO	2300-2100	2800	840-760	380	750-1100	-	-

Spesifikasi dapat berubah sewaktu-waktu tanpa pemberitahuan terlebih dahulu.
Untuk info lebih jelas mohon hubungi sales & marketing Outlet CKE sebelum melakukan transaksi.



www.cke.co.id

BROS/JZG/CKE/MC-DE MR-NO/NEW/2017/OKTOBER/26