



PRODUCT DESCRIPTION

Exhaust fans help ventilate and cool manholes, tanks and crawl spaces. Made using durable steel housing with a yellow finish. These two-speed blowers are lightweight and portable with an easy-carry handle. Powder coated steel blade guards enclose housing for safety. Rubber feet on base help minimize noise and reduce vibrations. Includes 10°L power cord. Ducting easily converts blower to an exhaust fan with convenient, flexible ducting. Ducts include quick-connect coupling for easy blower attachment. Ducts are made with 2-ply reinforced polyvinyl that is flame retardant and withstands -20° to 180°F temperatures. 120V. 1 Year Limited Warranty. Horsepower rating based upon maximum speed/load.

PRODUCT SPECIFICATION

| Code | Туре | Diameter | | Power | Speed | Air Flow | Current | | Noise |
|----------------|--------------|----------|-----|-------|-------|----------|---------|-----|-------|
| | | Inch | mm | Watt | RPM | m³/h | V | H'z | dB |
| PV-S08/0,18 | PV-(S)-08/15 | 8" | 200 | 130 | 2800 | 1505 | 220 | 50 | 70 |
| PV-\$10/32 | PV-(S)-10/32 | 10" | 250 | 220 | 2800 | 2584 | 220 | 50 | 72 |
| PV-S12/52-50HZ | PV-(S)-10/32 | 12" | 300 | 310 | 2800 | 2584 | 220 | 50 | 72 |
| PV-S14/75 | PV-(S)-12/52 | 14" | 350 | 750 | 2800 | 3604 | 220 | 50 | 75 |
| PV-S16/1 | PV-(S)-16/1 | 16" | 400 | 1200 | 2800 | 5401 | 220 | 50 | 79 |
| PV-S18/1 | PV-(S)-18/1 | 18" | 450 | 1800 | 2800 | 7511 | 220 | 50 | 82 |

ILLUSTRATION













The fan is suitable for air extraction, dust collection, fresh air supply in such locations as undergroudn warehouses, tunnels, chemical labs, ship's cabins and etc



Contact Us

4-92/2 28-2999 26-116-11849

Specification Can Change without Notification any Further

BROS/CKE/PV/NEW/2016/OKT/03